



# PT Tritools Indonesia

*Specialist In Plywood Industry*

Pusat Niaga Terpadu Daan Mogot Km 19,6

Blok A 8M Tangerang 15122

[www.tritoolsindonesia.co.id](http://www.tritoolsindonesia.co.id)

## Miscellaneous



Trimming Circular Saw



Photos for Illustration Purposes only



*Using Sanding Belt System*

*Using Trimming Circular Saw System*

## Specifications

PRE - Scarf Jointer	
Model	PRE SJC 1 + 3 – HX - T
Working Speed	0 ~ 40 m/min
Working Thickness Range	1.0 ~ 6.0 mm
Adjustable Work Angle	0° ~ 15 °
Saw Blade Dimension	250 x 2.4 x 1.8 x 25.4 x 40T (Outer Dia x Thickness x Bore x Nos of teeth)
Sanding Belt (Grit / size)	#40 ~ #60 / 45 x 1,380 mm
Speed of Emery Cloth	2,350 m/min
RPM of Pinch Roller	6,580 rpm
Motor Power	2.2 x 3 + 1.5 + 3 = 11.10 KW
Overall Dimension (L x W x H)	3,500 x 1,180 x 1,700 mm
Net Weight	1,500 kg

PRE - Line Press	
Working Veneer Width	1,400mm
Hot Platen (L x W x H)	1,400 x 70 x 50 mm
Compress Air Pressure	0.4 ~ 0.6 MPa (3 x Pneumatic Cylinders)
Total Power	1.8 x 2 Kw
Working Stroke	60 mm
Cylinder Diameter	Ø 160 x 3 pcs
Size of Machine (L x W x H)	1,760 x 1,130 x 1,820 mm
Net Weight	800 kg
Technical Requirement for Hot Press	1) Temperature: 110 - 150 °c
(Dependent on Glue Type)	2) Duration: 10-25 s

### Note :

*Technical specification subjected to change without prior notice  
Available other models. please contact us for more details*



Tritoolsindonesia



Tritools indonesia



0811-1231-291



Tritools Indonesia Official